1923 DIGI-MET® 3 point internal micrometers

IP 52 | DIN 863-4

Model

- DIN 863-4
- Reading: 0.001 mm / .00005 inch
- Protection class IP52
- LCD display 8.5 mm
- Ratchet stop
- For through holes
- From measuring range 12 mm for through and blind holes
- From measuring range 12 mm with carbide tipped measuring faces

Functions

- ON / OFF
- Set to zero at any point
- mm / inch switching
- ABS (display can be set to zero without losing the Preset value)
- **Q**uick-**L**ock (key lock)
- PRESET-Function (setting a numerical value)
- Variable data output RS 232 + Digimatic + USB

Delivery

- Plastic case
- Incl. setting ring
- Calibration certificate for setting ring and micrometer

Inclusive!

⋈		Measuring range mm	Measuring depth mm	Error limit µm	Order no.	List price EUR
▪		6 - 8	58	4	1923 510	1239.00
▪		8 - 10	58	4	1923 512	1239.00
▪		10 - 12	58	4	1923 514	1251.00
▪		12 - 16	64	4	1923 516	1251.00
▪		16 - 20	64	4	1923 518	1304.00
▪		20 - 25	68	4	1923 520	1327.00
▪		25 - 30	68	4	1923 522	1339.00
▪		30 - 40	76	4	1923 524	1398.00
▪		40 - 50	76	4	1923 526	1404.00
▪		50 - 60	79	5	1923 528	1510.00
▪		60 - 70	79	5	1923 530	1544.00
▪		70 - 85	97	5	1923 532	1579.00
▪		85 - 100	97	5	1923 534	1639.00
▪		100 - 125	132	6	1923 536	1991.00
▪		125 - 150	132	6	1923 538	2226.00
▪		150 - 175	132	7	1923 540	2397.00
▪		175 - 200	132	7	1923 542	2602.00



1998720 1998501 1997501

Accessories	Order no.	List price EUR
Data cable DATA VARIABLE to RS232	1997 501	57.00
Data cable DATA VARIABLE to digimatic	1998 501	73.00
Data cable DATA VARIABLE to USB	1998 720	82.00

Marked ▪ = excess length/excess weight

Marked ▪ = includes a F.O.C. calibration certificate, traceable to national standards